

1 TITLE OF THE INVENTION

2 DIAGNOSTIC APPARATUS FOR VALVE TIMING CONTROL SYSTEM

3

4 BACKGROUND OF THE INVENTION

5 1. Field of the invention

6 The present invention relates to a diagnostic apparatus
7 for a valve timing control system, particularly for a valve timing
8 control system in which a rotational phase between a crankshaft
9 and a camshaft of an internal combustion engine is designed so
10 as to change.

11 2. Discussion about prior arts

12 In recent years, an engine incorporating a valve timing
13 control system in which a rotational phase between a crankshaft
14 and a camshaft of the engine is adjustable, has been put into
15 practical use. Generally, the valve timing control system has
16 a variable valve timing mechanism for continuously varying at
17 least either of an intake valve timing and an exhaust valve timing.

18 Since the valve timing is one of very important engine
19 parameters, the valve timing control system needs a diagnostic
20 apparatus in case of failures. For example, Japanese Patent
21 Application Laid-open No. Toku-Kai-2001-20798 discloses a
22 technique in which frequency of misfires is monitored for every
23 operating area and in case where the frequency of misfires is
24 high only at a low speed and low load operating area, it is judged
25 that the high speed cam on the exhaust side is stuck, and in case

1 where the frequency of misfires is high at low speed and low load
2 operating areas and at intermediate speed and intermediate load
3 operating areas, it is judged that the high speed cam on the intake
4 side is stuck.

5 However, according to the technology wherein the
6 frequency of misfires is calculated for every operating area of
7 the engine as described in Toku-Kai-2001-20798, a burden of the
8 calculation of the frequency on the computer increases and has
9 such adverse effects as delays in judgments, detection errors
10 and the like. Further, since the misfire judgments are made only
11 at low speed and low load operating areas and at intermediate
12 speed and intermediate load, there is a disadvantage that the
13 range of diagnoses is restricted.

14

15 SUMMARY OF THE INVENTION

16 It is an object of the present invention to provide
17 a diagnostic apparatus for a valve timing control system capable
18 of enlarging the range of diagnoses and swiftly, securely detecting
19 failures of the valve timing control system.

20 A diagnostic apparatus of a valve timing control system
21 in which a valve timing is variably controlled by changing a
22 rotational phase between a crankshaft and a camshaft of an engine,
23 comprises means for detecting a fluctuation of engine speeds of
24 the engine following a change of engine operating conditions and
25 for calculating a diagnosis value based on the fluctuation; and

1 means for comparing the diagnosis value with a preestablished
2 threshold value and for judging that a failure occurs in the valve
3 timing control system, in case where the diagnosis value exceeds
4 the threshold value.

5

6 BRIEF DESCRIPTION OF THE DRAWINGS

7 Fig. 1 is a diagrammatic illustration showing an engine
8 incorporating a variable valve timing mechanism according to a
9 first embodiment of the present invention;

10 Fig. 2 is a flowchart of a diagnosis routine according
11 to the first embodiment of the present invention; and

12 Fig. 3 is a flowchart of a diagnosis routine according
13 to a second embodiment of the present invention.

14

15 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

16 Referring now to Fig. 1, first an overall construction
17 of an engine incorporating a variable valve timing mechanism will
18 be described. Reference numeral 1 denotes an engine, in this example,
19 a horizontally opposed four cylinder engine having a cylinder
20 block 1a divided into a left (right side of the drawing) and right
21 (left side of the drawing) bank around a crankshaft 1b. A cylinder
22 head 2 is mounted on the left and right banks of the cylinder
23 block 1a, respectively. The respective cylinder heads 2, 2 have
24 a set of an intake port 2a and an exhaust port 2b formed per each
25 cylinder.

1 The intake port 2a of the respective cylinder heads
2 2, 2 communicates with an intake manifold 3 on the upstream side.
3 The intake manifold 3 has an air chamber 4 in such a manner as
4 integrating intake passages of the respective cylinders. Further,
5 the air chamber 4 communicates with a throttle chamber 5 on the
6 upstream side. A throttle valve 5a interlocking with an
7 accelerator pedal (not shown) is disposed in the throttle chamber
8 5 and an air cleaner 7 is disposed on an intake pipe 6 upstream
9 of the throttle chamber 5. Further, a chamber 8 is disposed on
10 the intake pipe 6 upstream of the air cleaner 7.

11 Further, the intake pipe 6 is furnished with a bypass
12 passage 9 in a manner bypassing the throttle valve 5a and an idle
13 speed control valve 10 is interposed on the bypass passage 9.
14 The idle speed control valve 10 is for controlling the idle speed
15 by adjusting the amount of bypass air flowing through the bypass
16 passage 9.

17 Further, a fuel injector 11 is disposed directly
18 upstream of the intake port 2a of the respective cylinders and
19 a spark plug 12 is disposed in the respective cylinders with its
20 electrode exposed to a combustion chamber. The respective spark
21 plugs 12 are connected with an ignitor built-in type ignition
22 coil 13.

23 Farther, the respective exhaust ports 2b of the cylinder
24 head 2 are connected with an exhaust manifold 14 and an exhaust
25 pipe 15 is connected with a bifurcated portion of the exhaust

1 manifold 14. Further, a catalytic converter 16 and a muffler 17
2 are interposed on the exhaust pipe 15 in this order, respectively.

3 The respective cylinder heads 2 of the left and right
4 banks have an intake camshaft 19 and an exhaust camshaft 20 therein.
5 The rotation of the crankshaft 1b is transmitted to the intake
6 camshafts 19, 19 and the exhaust camshafts 20, 20 of the left
7 and right banks with 2:1 rotation ratio through a crank pulley
8 21 secured to the crankshaft 1b, a timing belt 22, left and right
9 intake cam pulleys 23, 23 and left and right exhaust cam pulleys
10 24, 24, respectively. Thus transmitted rotation of the camshafts
11 19, 20 gives the opening and closing motions to an intake valve
12 25 and an exhaust valve 26 through an intake cam (not shown)
13 provided on the intake camshaft 19 and an exhaust cam (not shown)
14 provided on the exhaust camshaft 20, respectively.

15 A hydraulically operated variable valve timing
16 mechanism 27 in which a rotational phase (displacement angle)
17 of the intake camshaft 19 to the crankshaft 1b is continuously
18 varied by the relative rotation between the intake cam pulley
19 23 and the intake camshaft 19, is disposed between the intake
20 cam shaft 19 and the intake cam pulley 23 of the respective banks.
21 In this embodiment, since the variable valve timing mechanism
22 27 is incorporated only on the intake camshaft 19, the intake
23 valve 25 opens and closes at variable valve timings according
24 to operating conditions of the engine 1 with respect to the fixed
25 valve timing of the exhaust valve 26.

1 Further, a flow control valve 28 for adjusting the
2 pressure of working fluid supplied by a hydraulic pump (not shown)
3 is equipped with the variable valve timing mechanism 27. The flow
4 control valve 28 is for example a spool valve duty-controlled
5 by an electronic control unit (hereinafter referred to as "ECU")
6 50 constituted by a micro-computer and the like. The spool valve
7 has a spool traveling in an axial direction of the flow control
8 valve 28 for changing over respective ports communicating with
9 an advance chamber (hydraulic chamber for advancing valve timing)
10 and a retard chamber (hydraulic chamber for retarding valve
11 timing) of the variable valve timing mechanism 27 and for adjusting
12 hydraulic pressure fed to those advance and retard chambers.
13 The detailed construction of the variable valve timing mechanism
14 27 is described in Japanese Patent Application No. Toku-Kai
15 2000-97096 by the inventor of the present invention.

16 Describing sensors equipped with the engine 1, an air
17 flow sensor 30 using a hot wire or a hot film is interposed on
18 the intake pipe 6 directly downstream of the air cleaner 7. Further,
19 a throttle opening angle sensor 31 is interlocked with a throttle
20 valve 5a disposed in a throttle chamber 5. Further, an oil
21 temperature sensor 32 is disposed in an oil pan 1c of the engine
22 1 and a water temperature sensor 34 is disposed in a water jacket
23 33 communicating between the left and right banks of the cylinder
24 block 1a. Further, an oxygen sensor 35 is disposed upstream of
25 the catalytic converter 16.

1 Further, a crank rotor 36 is mounted on the crankshaft
2 1b of the engine 1 and a crank angle sensor 37 is attached to
3 the cylinder block 1a opposite to protrusions provided on the
4 outer periphery surface of the crank rotor 36. Further, a cylinder
5 identifying sensor 38 is attached to the cylinder head 2 (in
6 this embodiment left bank) opposite to protrusions provided on
7 the rear surface of the intake cam pulley 23 which rotates at
8 a rotation ratio 1/2 of the crankshaft 1b.

9 Output signals of those sensors are inputted to the
10 ECU 50 and are processed therein. The ECU calculates miscellaneous
11 control parameters for the fuel injector 11, the ignitor built
12 in the ignition coil 13, the idle speed control valve 10, the
13 flow control valve 28 of the variable valve timing mechanism 27
14 and the like. Based on these control parameters, various engine
15 controls such as fuel injection control, ignition timing control,
16 idle speed control, valve timing control and the like are performed.

17 First, describing the valve timing control, a target
18 valve timing, namely, a control target value of the phase difference
19 between the rotation angles of the crankshaft 1b and the intake
20 cam shaft 19, is established on the basis of the engine operating
21 conditions, for example, engine speeds and engine loads. Then,
22 an actual valve timing, namely, a phase difference between the
23 actual rotation angles of the crankshaft 1b and the intake cam
24 shaft 19, is calculated based on crank pulses indicative of the
25 crank angle outputted from the crank angle sensor 37 and cam

1 position pulses indicative of the cam position outputted from
2 a cam position sensor 40. Then, the variable valve timing mechanism
3 27 is feedback-controlled through the flow control valve 28 so
4 that the actual valve timing agrees with the target valve timing.

5 Further, the ECU 50 makes periodical diagnoses of the
6 valve timing control system including the variable valve timing
7 mechanism 27, the flow control valve 28 and its control device.
8 Objects of diagnosis include exacerbated responseability due to
9 the defective sliding performance of miscellaneous sliding
10 sections, stickings due to jams of foreign matters and the like.

11 That is, when failures such as exacerbated
12 responseability and stickings occur in the valve timing control,
13 incomplete combustions including misfires are generated by the
14 deviation of valve timings of the respective cylinders from an
15 optimum condition. As a result, the engine speed has fluctuations.
16 Accordingly, the diagnosis of the valve timing control system
17 is to detect the deviation from the optimum condition by monitoring
18 such fluctuations of engine speeds.

19 The diagnosis of the valve timing control system will
20 be described by reference to a flowchart of a diagnostic routine
21 as illustrated in Fig. 2.

22 This diagnostic routine is executed every specified
23 time or every specified interval. At a step S101, it is judged
24 whether or not a misfire diagnosis condition, for example, a
25 condition that any fuel cut is not executed, is satisfied in the

1 present operating condition.

2 In case where the misfire diagnosis condition is not
3 satisfied, the program leaves the routine without carrying out
4 the diagnosis of the valve timing control system. In case where
5 the misfire diagnosis condition is satisfied, the program goes
6 to a step S102 where it is judged whether or not a valve timing
7 diagnosis condition is satisfied. The valve timing diagnosis
8 condition includes, for example, a state in which the engine speed
9 Ne or the intake manifold pressure PM is stable.

10 As a result, in case where the valve timing diagnosis
11 condition is not satisfied, the program leaves the diagnostic
12 routine without carrying out the diagnosis of the valve timing
13 control system. On the other hand, in case where the valve timing
14 diagnosis condition is satisfied, the program goes to the step
15 S102 to a step S103 where it is judged whether or not fluctuations
16 of engine speeds are within a specified range.

17 According to the valve timing control of the present
18 invention, for example, in an idling condition (low load low speed
19 condition), the opening and closing timing of the intake valve
20 25 is set to a most retarded angle, or advance angle = 0, to realize
21 the stability of the idle speed by getting rid of a valve overlap
22 of the exhaust valve 26 and the intake valve 25.

23 Further, in a mid-load area, the target valve timing
24 is established to a small to intermediate advance angle and the
25 opening and closing timing of the intake valve 25 is controlled

1 on the advance side. As a result, the valve overlap of the exhaust
2 valve 26 and the intake valve 25 increases to enhance fuel economy.
3 Further, in a high load area, the target valve timing is established
4 to a largest advance and the opening and closing timing of the
5 intake valve 25 is controlled on a further advance side. As a
6 result, the valve overlap of the exhaust valve 26 and the intake
7 valve 25 further increases to raise engine power. Further, in
8 a low load and high speed area, the target valve timing is
9 established to a small advance angle and the opening and closing
10 timing of the intake valve 25 is controlled on the retard side.
11 As a result, the valve overlap increases to prevent an overrun
12 of the engine speed.

13 Accordingly, when the engine operating condition
14 changes, for example, when a traveling condition transfers to
15 an idle condition, the target valve timing changes from the advance
16 side to the retard side and as a result fluctuations of engine
17 speeds are generated due to a sudden change in torque. These
18 fluctuations of engine speeds are relatively small in case where
19 the variable valve timing control system is normal, however, in
20 case where the variable valve timing control system has an abnormal
21 operation, the fluctuations are enlarged. Particularly, in case
22 of the engine 1, large fluctuations of engine speeds occur due
23 to torque differences generated between the bank having some
24 defects in the valve timing control system and the bank having
25 no failure. The fluctuations behave just like in case of misfires.

1 In general, whether the misfire is generated or not
2 is judged from the change of the difference of the engine speeds
3 between a cylinder in the present combustion stroke and a cylinder
4 in a previous combustion stroke. If this change of the engine
5 speed difference between a cylinder in a second previous
6 combustion stroke and the cylinder in the previous combustion
7 stroke is a negative value below a judgment criteria and the change
8 of the engine speed difference between the cylinder in the
9 previous combustion stroke and the cylinder in the present
10 combustion stroke is a positive value above the judgment criteria,
11 it is judged that the cylinder in the previous combustion stroke
12 is in a misfire condition. An absolute value of the change of
13 the engine speed difference, that is, the misfire diagnosis value
14 is used as a diagnostic value DIAG for diagnosing the valve timing
15 control system. The failure of the valve timing control system
16 can be judged by monitoring this diagnostic value DIAG.

17 At a step 103, the diagnostic value DIAG is compared
18 with a preestablished judgment threshold value DIAGSET. The
19 judgment threshold value DIAGSET is a value for specifying that
20 the valve timing control system operates in a normal range and
21 is determined by simulations, experiments and the like in
22 consideration of miscellaneous characteristics of the engine and
23 the variable valve timing mechanism 27.

24 In case of $DIAG \leq DIAGSET$, the program goes to a step
25 S104 in which it is judged that the valve timing control system

1 is normal and leaves the routine. In case of $DIAG > DIAGSET$, the
2 program goes to a step S105 where it is judged that there is a
3 failure in the valve timing control system. Then, failure data
4 are stored in a backup memory and an alarm is given to a driver,
5 leaving the routine.

6 The diagnosis value $DIAG$ may be an integral value of
7 the misfire diagnosis values (absolute value), that is, an
8 integral value of changes of the engine speed. This integral value
9 is compared with a judgment threshold value. If this integral
10 value exceeds the judgment threshold value, it may be judged that
11 the valve timing control system is abnormal.

12 According to the embodiment, when the displacement of
13 the engine speed or the integral value of the engine speeds in
14 changing the engine operating conditions exceeds a judgment
15 threshold value, since it is judged that the valve timing control
16 system is abnormal, sliding failures of the sliding sections of
17 the valve timing mechanism 27 or sticking failures can be swiftly
18 and securely detected, irrespective of the areas where the engine
19 is operative. These failures of the sliding sections and sticking
20 failures bring higher hydraulic pressure than specified and as
21 a result the responseability of the actual advance is exacerbated.

22 Fig. 3 is a flowchart of a diagnostic routine according
23 to a second embodiment of the present invention.

24 According to the first embodiment described above, the
25 failures of the valve timing control system are judged by whether

1 the magnitude of the fluctuations of engine speeds following the
2 change of the engine operating conditions exceeds a specified
3 level or not. On the other hand, according to the second embodiment,
4 the failures are judged by monitoring an elapsed time until the
5 fluctuation of the engine speeds converges.

6 Therefore, according to the second embodiment, after
7 the same processes as in the diagnostic routine of the first
8 embodiment are performed in steps S201 and S202, that is, after
9 the misfire diagnosis condition and the valve timing diagnosis
10 condition are satisfied respectively, the program goes to a step
11 S203 where it is investigated whether or not the fluctuation Δ
12 N of the engine speeds (misfire diagnosis value) following the
13 change of the engine operating conditions exceeds a preestablished
14 value NSET. The preestablished value NSET is a value which can
15 be deemed to converge into a specified value.

16 As a result of the investigation at S203, in case of
17 $\Delta N \leq NSET$, the program goes to a step S206 where a timer C for
18 measuring a time until the fluctuation of engine speed converges
19 is cleared ($C \leftarrow 0$) and at a step S207 it is judged that the valve
20 timing control system is normal, the program leaving the routine.

21 On the other hand, in case of $\Delta N > NSET$, the program
22 goes from the step S203 to a step S204 where the timer C is counted
23 up ($C \leftarrow C+1$) and at a step S205 it is checked whether or not the
24 timer C exceeds a preestablished time CSET. The time CSET is a
25 maximum time needed for the convergence of the fluctuation of

1 the engine speed and is obtained from prior simulations or
2 experiments in consideration of characteristics of the engine
3 or the variable valve timing mechanism 27.

4 At the step S205, in case of $C \leq CSET$, the program leaves
5 the routine through the steps S206 and S207. In case of $C > CSET$,
6 that is, in case where the fluctuation of the engine speed
7 following on the change of engine operating conditions does not
8 converge after the preestablished time elapses, the program goes
9 to a step S208 in which it is judged that the fluctuation does
10 not still converge and there is a failure in the valve timing
11 control system, leaving the routine. Then, the failure data is
12 stored in a back-up memory for diagnosis and is warned to a driver.

13 The entire contents of Japanese Patent Application No.
14 Tokugan 2003-090724 filed March 28, 2003, is incorporated herein
15 by reference.

16 While the present invention has been disclosed in terms
17 of the preferred embodiments in order to facilitate better
18 understanding of the invention, it should be appreciated that
19 the invention can be embodied in various ways without departing
20 from the principle of the invention. Therefore, the invention
21 should be understood to include all possible embodiments which
22 can be embodied without departing from the principle of the
23 invention set out in the appended claims.

24